



225 Lincoln Highway Suite 167

Fairless Hills, PA 19030

Ph 215 547-2570 Fx 217 701-9197

service@sandiesusa.com

MODEL 343 LIGHT BOX INSTRUCTION

- 1) When unpacking light box DO NOT remove diffuser and label piece from inside red Plexiglas enclosure.
- 2) Connect DC plug to 12/24VDC supply using 2.5mm plug provided. Center position is hot..
- 3) Mount light box frame against wall on either an electrical box or directly onto drywall or concrete using wall anchors.
- 4) Place red Plexiglas and diffuser lens into light frame. (ensure Plexiglas is seated properly into frame)
- 5) Place cap on top of Plexiglas and secure with two 4-40 screws provided



225 Lincoln Highway Suite 167

Fairless Hills, PA 19030

Ph 215 547-2570 Fx 217 701-9197

service@sandiesusa.com

MODEL 343 LIGHT BOX INSTRUCTION

- 1) When unpacking light box DO NOT remove diffuser and label piece from inside red Plexiglas enclosure.
- 2) Connect DC plug to 12/24VDC supply using 2.5mm plug provided. Center position is hot..
- 3) Mount light box frame against wall on either an electrical box or directly onto drywall or concrete using wall anchors.
- 4) Place red Plexiglas and diffuser lens into light frame. (ensure Plexiglas is seated properly into frame)
- 5) Place cap on top of Plexiglas and secure with two 4-40 screws provided

